

JARCRAC MULTI

Powerful, economical and versatile.

The Multi is suitable for rugged terrain such as soft swamps and ditched areas. The long suspension and the swing structure of it allows smooth working in uneven terrain.

The accessory possibilities are versatile. The Multi can be equipped, for example, with a three-way hitch, a loading space and a power take-off, which allows the use of wide range of work equipment.

This type of machine has good user experiences, including electricity companies, which pass through electricity lines in different terrain.



Technical specifications

Motor: Doosan 1,8 l (45 kW) or Doosan 2,4 l (55,4 kW) RPM adjustment: electric, via potentiometer Fuel tank: 70 l

Electric system: Voltage: 12 V Alternator: 85 A Battery: 95 Ah

Transmission and hydraulics: Drive pumps: 2x28 cm3 (Bondioli&Pavesi) Drive motors: 2 x 250/500 cm3 (Poclain) Work pump: 26 - 56 cc, 195 bar LS (Bondioli&Pavesi)

Dimensions: Length: 310 cm, width: 204 cm and height: 242 cm Weigth: appx. 2500 kg Ground clearance: 47 cm Speed: 2 speed ranges: 0-6 km/h and 0-12 km/h

Chassis and tracks: Swinging bogies (2 per side) Track width: 55 cm Track material: rubber/textile-mix, steel shoes

Radio and heater as standard. 4000kg capacity forest trailer with Palms 2.54 crane and electric control is also available. Ask more about the broad accessory options.